



ALMATIS

PREMIUM ALUMINA



Americas Regional Product Data

TABALOX[®] 3-6 Mesh

Tabalox is designed for use in aluminum filtration. It is specially processed to remove dust and chips that would carry through into the metal.

Chemical Composition (%)	Typical	Min	Max
Na ₂ O			0.40
SiO ₂			0.09
Fe magnetic			0.02
Physical Properties	Typical	Min	Max
Bulk Specific Gravity (gm/cm ³)		3.50	
Apparent Porosity (%)			5
Water Absorption (%)			1.5
Screen (%)	Typical	Min	Max
+6.3 mm	0	0	4
+5.0 mm	30		
+4.0 mm	39		
-2.0 mm	0	0	3
Standard Packaging	2000 lb super sacks - 1 per pallet		

Chemistry for all products is assured through process control and verification of incoming alumina chemistry. Each product is certified to conform to the chemistry specifications listed, thus each product lot is not tested.

All data is based upon Almatris standard test methods. All test methods are available upon request. The typical properties are based upon the actual averages from production data. The Min/Max data represents Almatris standard product specification data for these products.



Contacts for sales, technical information and application assistance

Almatris GmbH
Lyoner Straße 9
60528 Frankfurt/Germany
Phone **49 69 957 341 0**
Fax **49 69 957 341 13**

info@almatris.com
www.almatris.com

Almatris, Inc.
501 West Park Road
Leetsdale, PA 15056,
USA
☎ **800 643 8771** (within US)
☎ **1 412 630 2800** (outside US)
☎ **1 412 630 2900**

Almatris do Brasil Ltda.
Avenida Jose de Souza
Campos, 243
2° Andar – Cambuí
13025-320 – Campinas,
SP – Brasil
☎ **55 19 3515-1400**
☎ **55 19 3515-1410**

MSDS 154