



**Global Product Data Sheet** 

# Calcium Aluminate Cement CA-670

# **Product Properties**

- CA-670 is the newest Almatis 70% alumina cement
- CA-670 is characterized by high early strength
- Additive-free
- Good workability
- Low water demand
- Available in plastic 25 kg bags
- 24-month shelf life

Chemical Composi	tion	Typical	min.	max.		
CaO	[%]	29	28	31		
Al <sub>2</sub> 0 <sub>3</sub>	[%]	70	69			
Na <sub>2</sub> O	[%]			0.3		
SiO <sub>2</sub>	[%]			0.3		
$Fe_2O_3$	[%]			0.2		
Mg0	[%]			0.4		
Fineness (Laser diffraction)						
-45 µm	[%]	97	95			
d50	μm	10				

All data are based upon Almatis standard test methods.

The typical properties are based upon the actual averages from production data.



# **Cement Properties in NORTAB Mortar**

Water addition: 10%							
Vicat Setting Time		Typical	Min.	Max.			
Initial Set	[min]	350	300				
Final Set	[min]	375	330	460			
Exothermic Reaction Time							
EXO + 5	[min]	375					
EXO Max	[min]	445					
Vibration Flow							
F10	[cm]	18	15				
F30	[cm]	18	14				
F60	[cm]	17	13				

Cold Modulus of Ruptu	ure (CMoR)	Typical	Min.	Max.			
24h Cured 20ºC	[MPa]	8	7				
24h Dried 105ºC	[MPa]	11	9				
5h Fired 1000ºC	[MPa]	5	3				
Cold Crushing Strength (CCS)							
24 h Cured 20ºC	[MPa]	56	45				
24h Dried 110ºC	[MPa]	80	55				
5h Fired 1000⁰C	[MPa]	39	25				

## Shelf life

Stored under adequate dry conditions and in the original packaging, the properties of all Almatis Calcium Aluminate Cements remain stable for a period of 24 months. Experience has shown that even after longer storage time the properties are not impaired. Exposure to ultraviolet radiation from direct sun light can alter the plastic foil and ultimately reduce the shelf life. An additional protection from direct sun light is required in such cases. The shrink wrap shall remain until the material is being used. Removal of the shrink wrap reduces the shelf life of the cement in big bags.

For more detailed information on Cement Testing please refer to the brochure "Cement Test Methods".

## Packaging available

25 kg plastic bags and 1 mt big bags

# Contacts for sales, technical information and application assistance

Almatis GmbH Giulinistrasse 2 67065 Ludwigshafen

Germany Phone 49 621 5707 0



Almatis GmbH Lyoner Strasse 9 60528 Frankfurt/Germany

info@almatis.com www.almatis.com

## Almatis B.V.

Theemsweg 30 3197KM Botlek RT The Netherlands

Phone 31 181 2701 00

## Qingdao Almatis Co. Ltd.

No.1 Song Hua Jiang Road Qingdao Economic & Technology Development Zone Qingdao, 266510 P.R. China

Phone 86 532 8572 8035

Almatis, Inc. 501 West Park Road Leetsdale, PA 15056, USA

Phone 1 412 630 2800

Almatis Alumina

**Private Limited** Kankaria Estate, 2nd Floor 6, Little Russell Street Calcutta 700-001, India

Phone 91 33 2242 7961

## Almatis Limited

Morimura Bldg. Toranomon Tower Office 13 F 1-28, Toranomon 4-chrome Minato-ku, Tokyo 105-8451 Japan

Phone 81 3 5510 66 88

## Almatis do Brasil Ltda.

Avenida Jose de Souza Campos, 243 2° Andar – Cambuí 13025-320 – Campinas, SP – Brasil

Phone 55 19 3515-1400

