



Americas Regional Product Data

Tabular Alumina T60/T64

-325 Mesh SP/XLS

Product Characteristics

Almatis Tabular Alumina T60/T64 is a pure sintered α -alumina material that has been fully densified by rapid sintering at temperatures in excess of 1800°C. Tabular Alumina has characteristic large, well developed hexagonal tablet shaped alumina crystals of up to 200 μ m length. Tabular alumina has extremely high refractoriness, high mechanical strength and abrasion resistance, very good chemical purity, excellent dielectric properties and good resistance against acid and alkali corrosion.

Product Applications

Almatis low-soda and ultra-low soda tabular aluminas combine the properties of standard tabular alumina together with a low alkali content to provide a product with higher dielectric strength, thermal conductivity and chemical inertness in the many applications. The most common applications for low and ultra-low soda ground tabular are ceramics, investment casting and functional filler/epoxy-resin systems. The extremely low total Na₂O content results in even lower solubility of free Na⁺, providing improved pH and viscosity stability, and longer slurry life in investment casting applications. The reduction in free Na⁺ also minimizes potential undesired chemical interactions between the alumina filler and matrix components in functional filler applications.

Chemical Composition (%)		- 325 Mesh SP		- 325 Mesh XLS		
Al ₂ O ₃ by difference		99.6 min		99.7 min		
Na ₂ O		0.20 max		0.05 max		
SiO ₂		0.09 max		0.09 max		
Fe magnetic		0.02 max		0.02 max		
Particle Size Distribution (%)		Typical	Min	Max	Min	Max
+0.063 mm		0.4		1		1
-0.045 mm		97	95		95	
Standard Packaging						
50 lb paper bags - 70 per pallet						

All data is based upon Almatis standard test methods. All test methods are available upon request.
 The typical properties are based upon the actual averages from production data.
 The Min/Max data represents Almatis standard product specification data for these products.



Tabular Alumina T60/T64

-325 Mesh SP/XLS



Contacts for sales, technical information and application assistance



Almatis GmbH
Lyoner Straße 9
60528 Frankfurt/Germany

Phone 49 69 957 341 0
Fax 49 69 957 341 13

info@almatis.com
www.almatis.com

Almatis, Inc.
501 West Park Road
Leetsdale, PA 15056,
USA

☎ 800 643 8771 (within US)
☎ 1 412 630 2800 (outside US)
☎ 1 412 630 2900

Almatis do Brasil Ltda.
Avenida Jose de Souza
Campos, 243
2° Andar – Cambuí
13025-320 – Campinas,
SP – Brasil
☎ 55 19 3515-1400
☎ 55 19 3515-1410

MSDS 154